

# acm M 2800

## Description

The M Series professional power amplifiers offer ACM renowned integrity and can handle exceptionally high power ratings in a compact, light weight 3RU package. The M Series amps also feature Automatic Clip Limiting to protect connected drivers; Impedance sensing to accommodate varying impedance outputs; tunnel-cooled, high efficiency heat sinks; and variable-speed DC fans to limit the operating temperature and extend amplifier life.

	8 Ohm stereo	4 Ohm stereo	2 Ohm stereo	8 Ohms bridged	4 Ohms bridged	Weight
M2800	800W	1200W	1500W	2400W	—	32kg
M2800.2	800W	1200W	1800W	2400W	3600W	35kg
M21200	1200W	1800W	2200W	3600W	—	36kg



**M 2800** acm **acmaudio** Professional Power Amplifier  
www.acmaudio.com



acm acmaudio

# M 2800 Professional Power Amplifier



## Specifications

**Rated power bridge mode 8 Ohms**  
2400Watts @ 1 kHz at <0.5% T.H.D.

**Rated power (2 X 4 Ohms)**  
1200 Watts per channel @ 1 kHz at <0.5% T.H.D. both channels driven

**Rated power (2 X 8 Ohms)**  
800 Watts per channel @ 1 kHz at <0.5% T.H.D. both channels driven

**Input CMRR**  
>-65 dB @ 1 kHz

**Power bandwidth**  
20 Hz - 20kHz; +0, -0.5 dB at rated 200 Watts 8 Ohm power

**T.H.D.(2 X 4 Ohms)**  
<0.05% @ 600 Watts per channel from 20 HZ to 20 kHz

**T.H.D.(2 X 8 Ohms)**  
<0.05% @ 400Watts per channel from 20 HZ to 20 kHz

**Rated power (1 X 4 Ohms)**  
1300 Watts @ 1 kHz at <0.5% T.H.D.

**Rated power (1 X 8 Ohms)**  
860 Watts @ 1 kHz at <0.5% T.H.D.

**Minimum load impedance**  
2 Ohms

**Maximum RMS voltage swing**  
93Volts

**Frequency response**  
10 Hz - 50 kHz; +0, -3 dB at 1 Watt

**Phase response**  
+20° to -25° from 20 Hz to 20 kHz

**Input impedance**  
20 k Ohms, balanced; 10k Ohms, unbalanced

**Cooling**  
Low temperature dependant variable speed 120mm high output DC fans

**Controls**  
Two front panel attenuators, rear panel mode switch and gain select switch

**Voltage gain**  
0.775V, 32 dB or 26 dB

**Crosstalk**  
>-60 dB @ 1 kHz at rated power @ 8 Ohms

**Hum and noise**  
>-104 dB, "A" weighted referenced to rated power @ 8 Ohms

**Slew rate**  
>25V/us

**Damping factor (8 Ohms)**  
>800:1 @ 20Hz - 1 kHz

**Indicator LEDs**  
2 Clip, 2 signal presence, 2 active status, 2 Protection

**Protection**  
Thermal, DC, turn-on bursts, incorrect loads

**Connectors**  
XLR, Speakon and Binding Post speaker output, 240/230 Volt 20 amp IEC mains

**Construction**  
16 ga. Steel

**Dimensions**  
132mm x 483 mm x 498 mm

**Net weight**  
32kg

**Gross weight**  
35kg